



DVDM Calibrated, Filtered Gamma Ray (GRMA_FILT)		
0	(GAPI)	150
Rate of Penetration, Averaged over Last 5ft (ROP5_RM)		
100	(M/HR)	0

ARC Blended Phase-Shift Resistivity 16-in. (P16B)		
0	(OHMM)	10
ARC Blended Phase-Shift Resistivity 40-in. (P40B)		
0	(OHMM)	10

ARC Attenuation Conductivity 40-in. at 2 MHz (A40H_COND)		
4000	(MM/M)	0
Downhole Annulus Pressure (DHAP)		
1000	(PSI)	3000

ARC Amplified Blended Phase-Shift Resistivity 40-in (P40B)		
0	(OHMM)	2

Downhole Annulus Temperature (DHAT)		
0	(DEGC)	10

ARC Blended Attenuation Resistivity

ARC Blended Attenuation Resistivity
40-in. (A40B)
0 (OHMM) 10

IDEAL Version: ID10_2B_08
IDF

Company: Lamont-Doherty Borehole Research

Schlumberger

Well: IODP Expedition 311 CAS-01B

Field: Cascadia Margin

Rig: JOIDES Resolution

State: Pacific Ocean

EcoScope Resistivity - Blended
1:1200 Measured Depth
Recorded Mode Log