

# Schlumberger

Company: Lamont Doherty

Well: ODP Leg 201, Site 1228A PRU-2A

Field: Peru Margin

Rig: JOIDES Resolution Ocean: Pacific

## Natural Gamma Ray Spectroscopy (HNGS)

JOIDES Resolution			
Peru Margin			
Field: ODP Leg 201, Site 1228A PRU-2			
Rig: Location: 11 Deg 53.900' S Latitude			
Rig: Well: Company: Lamont Doherty	LOCATION	API Serial No.	Max Hole Devi.
Logging Date	5-Mar-2002	Longitude	Latitude
Run Number	1		
Depth Driller	474 m		
Schlumberger Depth	475 m		
Bottom Log Interval	444 m		
Top Log Interval	277 m		
Casing Driller Size @ Depth	0.000 in @ 342 m		@
Casing Schlumberger	345 m		
Bit Size	11.438 in		
Type Fluid In Hole	Sepiolite/Saltwater		
MUD Density	1.07 g/cm3		
Fluid Loss	PH		
Source Of Sample	mudpit		
RM @ Measured Temperature	0.235 ohm.m @ 33 degC		@
RMF @ Measured Temperature	@		@
RMC @ Measured Temperature	@		@
Source RMF	RMC	none	none
RM @ MRT	RMF @ MRT	0.294 @ 22	@ 22
Maximum Recorded Temperatures	24.5 degC		
Circulation Stopped	Time	5-Mar-2002	16:00
Logger On Bottom	Time	5-Mar-2002	20:24
Unit Number	Location	99	Houston ODP
Recorded By		K. Swain	Gilles Guerin
Witnessed By			

Run 1 Run 2 Run

## DISCLAIMER


THE USE OF AND RELIANCE UPON THIS RECORDED-DATA BY THE HEREIN NAMED COMPANY (AND ANY OF ITS AFFILIATES, PARTNERS, REPRESENTATIVES, AGENTS, CONSULTANTS AND EMPLOYEES) IS SUBJECT TO THE TERMS AND CONDITIONS AGREED UPON BETWEEN SCHLUMBERGER AND THE COMPANY, INCLUDING: (a) RESTRICTIONS ON USE OF THE RECORDED-DATA; (b) DISCLAIMERS AND WAIVERS OF WARRANTIES AND REPRESENTATIONS REGARDING COMPANY'S USE OF AND RELIANCE UPON THE RECORDED-DATA; AND (c) CUSTOMER'S FULL AND SOLE RESPONSIBILITY FOR ANY INFERENCE DRAWN OR DECISION MADE IN CONNECTION WITH THE USE OF THIS RECORDED-DATA.

## EQUIPMENT DESCRIPTION

## RUN 1

## RUN 2

SURFACE EQUIPMENT		
WITM (DTS)-A		
SFT-281 24		
SFT-178 4722		
GSR-U 135		
GSR-U/Y		
 DOWNHOLE EQUIPMENT		
LEH-QT		
LEH-QT 1726		
DTC-H		
ECH-KC 9343		
SGT-N		
SGH-K 2448		
SGH-K 2520		
SGH-K 2522		
SGH-K 2524		
SGH-K 2526		
SGH-K 2528		
SGH-K 2530		
SGH-K 2532		
SGH-K 2534		
SGH-K 2536		
SGH-K 2538		
SGH-K 2540		
SGH-K 2542		
SGH-K 2544		
SGH-K 2546		
SGH-K 2548		
SGH-K 2550		
SGH-K 2552		
SGH-K 2554		
SGH-K 2556		
SGH-K 2558		
SGH-K 2560		
SGH-K 2562		
SGH-K 2564		
SGH-K 2566		
SGH-K 2568		
SGH-K 2570		
SGH-K 2572		
SGH-K 2574		
SGH-K 2576		
SGH-K 2578		
SGH-K 2580		
SGH-K 2582		
SGH-K 2584		
SGH-K 2586		
SGH-K 2588		
SGH-K 2590		
SGH-K 2592		
SGH-K 2594		
SGH-K 2596		
SGH-K 2598		
SGH-K 2600		
SGH-K 2602		
SGH-K 2604		
SGH-K 2606		
SGH-K 2608		
SGH-K 2610		
SGH-K 2612		
SGH-K 2614		
SGH-K 2616		
SGH-K 2618		
SGH-K 2620		
SGH-K 2622		
SGH-K 2624		
SGH-K 2626		
SGH-K 2628		
SGH-K 2630		
SGH-K 2632		
SGH-K 2634		
SGH-K 2636		
SGH-K 2638		
SGH-K 2640		
SGH-K 2642		
SGH-K 2644		
SGH-K 2646		
SGH-K 2648		
SGH-K 2650		
SGH-K 2652		
SGH-K 2654		
SGH-K 2656		
SGH-K 2658		
SGH-K 2660		
SGH-K 2662		
SGH-K 2664		
SGH-K 2666		
SGH-K 2668		
SGH-K 2670		
SGH-K 2672		
SGH-K 2674		
SGH-K 2676		
SGH-K 2678		
SGH-K 2680		
SGH-K 2682		
SGH-K 2684		
SGH-K 2686		
SGH-K 2688		
SGH-K 2690		
SGH-K 2692		
SGH-K 2694		
SGH-K 2696		
SGH-K 2698		
SGH-K 2700		
SGH-K 2702		
SGH-K 2704		
SGH-K 2706		
SGH-K 2708		
SGH-K 2710		
SGH-K 2712		
SGH-K 2714		
SGH-K 2716		
SGH-K 2718		
SGH-K 2720		
SGH-K 2722		
SGH-K 2724		
SGH-K 2726		
SGH-K 2728		
SGH-K 2730		
SGH-K 2732		
SGH-K 2734		
SGH-K 2736		
SGH-K 2738		
SGH-K 2740		
SGH-K 2742		
SGH-K 2744		
SGH-K 2746		
SGH-K 2748		
SGH-K 2750		
SGH-K 2752		
SGH-K 2754		
SGH-K 2756		
SGH-K 2758		
SGH-K 2760		
SGH-K 2762		
SGH-K 2764		
SGH-K 2766		
SGH-K 2768		
SGH-K 2770		
SGH-K 2772		
SGH-K 2774		
SGH-K 2776		
SGH-K 2778		
SGH-K 2780		
SGH-K 2782		
SGH-K 2784		
SGH-K 2786		
SGH-K 2788		
SGH-K 2790		
SGH-K 2792		
SGH-K 2794		
SGH-K 2796		
SGH-K 2798		
SGH-K 2800		
SGH-K 2802		
SGH-K 2804		
SGH-K 2806		
SGH-K 2808		
SGH-K 2810		
SGH-K 2812		
SGH-K 2814		
SGH-K 2816		
SGH-K 2818		
SGH-K 2820		
SGH-K 2822		
SGH-K 2824		
SGH-K 2826		
SGH-K 2828		
SGH-K 2830		
SGH-K 2832		
SGH-K 2834		
SGH-K 2836		
SGH-K 2838		
SGH-K 2840		
SGH-K 2842		
SGH-K 2844		
SGH-K 2846		
SGH-K 2848		
SGH-K 2850		
SGH-K 2852		
SGH-K 2854		
SGH-K 2856		
SGH-K 2858		
SGH-K 2860		
SGH-K 2862		
SGH-K 2864		
SGH-K 2866		
SGH-K 2868		
SGH-K 2870		
SGH-K 2872		
SGH-K 2874		
SGH-K 2876		
SGH-K 2878		
SGH-K 2880		
SGH-K 2882		
SGH-K 2884		
SGH-K 2886		
SGH-K 2888		
SGH-K 2890		
SGH-K 2892		
SGH-K 2894		
SGH-K 2896		
SGH-K 2898		
SGH-K 2900		
SGH-K 2902		
SGH-K 2904		
SGH-K 2906		
SGH-K 2908		
SGH-K 2910		
SGH-K 2912		
SGH-K 2914		
SGH-K 2916		
SGH-K 2918		
SGH-K 2920		
SGH-K 2922		
SGH-K 2924		
SGH-K 2926		
SGH-K 2928		
SGH-K 2930		
SGH-K 2932		
SGH-K 2934		
SGH-K 2936		
SGH-K 2938		
SGH-K 2940		
SGH-K 2942		
SGH-K 2944		
SGH-K 2946		
SGH-K 2948		
SGH-K 2950		
SGH-K 2952		
SGH-K 2954		
SGH-K 2956		
SGH-K 2958		
SGH-K 2960		
SGH-K 2962		
SGH-K 2964		
SGH-K 2966		
SGH-K 2968		
SGH-K 2970		
SGH-K 2972		
SGH-K 2974		
SGH-K 2976		
SGH-K 2978		
SGH-K 2980		
SGH-K 2982		
SGH-K 2984		
SGH-K 2986		
SGH-K 2988		
SGH-K 2990		
SGH-K 2992		
SGH-K 2994		
SGH-K 2996		
SGH-K 2998		
SGH-K 3000		
SGH-K 3002		
SGH-K 3004		
SGH-K 3006		
SGH-K 3008		
SGH-K 3010		
SGH-K 3012		
SGH-K 3014		
SGH-K 3016		
SGH-K 3018		
SGH-K 3020		
SGH-K 3022		
SGH-K 3024		
SGH-K 3026		
SGH-K 3028		
SGH-K 3030		
SGH-K 3032		
SGH-K 3034		
SGH-K 3036		
SGH-K 3038		
SGH-K 3040		
SGH-K 3042		
SGH-K 3044		
SGH-K 3046		
SGH-K 3048		
SGH-K 3050		
SGH-K 3052		
SGH-K 3054		
SGH-K 3056		
SGH-K 3058		
SGH-K 3060		
SGH-K 3062		
SGH-K 3064		
SGH-K 3066		
SGH-K 3068		
SGH-K 3070		
SGH-K 3072		
SGH-K 3074		
SGH-K 3076		
SGH-K 3078		
SGH-K 3080		
SGH-K 3082		
SGH-K 3084		
SGH-K 3086		
SGH-K 3088		
SGH-K 3090		
SGH-K 3092		
SGH-K 3094		
SGH-K 3096		
SGH-K 3098		
SGH-K 3100		
SGH-K 3102		
SGH-K 3104		
SGH-K 3106		
SGH-K 3108		
SGH-K 3110		
SGH-K 3112		
SGH-K 3114		
SGH-K 3116		




## Output DLIS Files


DEFAULT	PI_LDLAPS_NGS_005LUP	FN:6	PRODUCER	05-Mar-2002 20:24	475.5 M	255.9 M
REDUCE	PI_LDLAPS_NGS_005LUP	FN:7	PRODUCER	05-Mar-2002 20:24	475.5 M	255.9 M


## OP System Version: 10C0-306 MCM


DIT-E	10C0-306	HLDT-A	10C0-306
DTA-A	10C0-306	NPLC-B	10C0-306
APS-BA	10C0-306	HNGS-BA	10C0-306
SGT-N	10C0-306	DTC-H	10C0-306



### PIP SUMMARY











## Parameters

DLIS Name	Description	Value
BHS	DIT-E: Dual Induction - E	
GCSE	Borehole Status	OPEN
	Generalized Caliper Selection	CALI
BHS	APS-BA: Accelerator-Porosity Tool	
GCSE	Borehole Status	OPEN
	Generalized Caliper Selection	CALI
HNGS-BA: Hostile Natural Gamma Ray Sonde		
BAR1	HNGS Detector 1 Barite Constant	1
BAR2	HNGS Detector 2 Barite Constant	1
BHK	HNGS Borehole Potassium Correction Concentration	0
BHS	Borehole Status	OPEN
CSD1	Inner Casing Outer Diameter	0
CSD2	Outer Casing Outer Diameter	0
CSW1	Inner Casing Weight	0
CSW2	Outer Casing Weight	0
DBCC	HNGS Barite Constant Correction Flag	NONE
GCSE	Generalized Caliper Selection	CALI
H1P	HNGS Detector 1 Allow/Disallow In Processing	ALLOW
H2P	HNGS Detector 2 Allow/Disallow In Processing	ALLOW
HABK	HNGS Borehole Potassium Running Average	-0.00491096
HALF	HNGS Alpha Filter Length	60
HCRB	HNGS Apply Borehole Potassium Correction	NONE
HMWM	Mud Weighting Material	NATU
HNPE	HNGS Processing Enable	YES
S1BI	HNGS Detector 1 Calibration Bismuth Count Rate	1.3
S2BI	HNGS Detector 2 Calibration Bismuth Count Rate	1.3
SGRC	HNGS Standard Gamma-Ray Correction Flag	YES
TPOS	Tool Position	ECCE
VBA1	HNGS Detector 1 Variable Barite Factor Running Average	0.77628
VBA2	HNGS Detector 2 Variable Barite Factor Running Average	0.814463
SGT-N: Scintillation Gamma-Ray - N		
BHS	Borehole Status	OPEN
GCSE	Generalized Caliper Selection	CALI
HOLEV: Integrated Hole/Cement Volume		
BHS	Borehole Status	OPEN
GCSE	Generalized Caliper Selection	CALI
System and Miscellaneous		
BS	Bit Size	11.438
DFD	Drilling Fluid Density	1.07

Format: HNGSYields Vertical Scale: 1:200 Graphics File Created: 05-Mar-2002 20:24

OP System Version: 10C0-306  
MCM

DIT-E	10C0-306	HLDT-A	10C0-306
DTA-A	10C0-306	NPLC-B	10C0-306
APS-BA	10C0-306	HNGS-BA	10C0-306
SGT-N	10C0-306	DTC-H	10C0-306

## Output DLIS Files

DEFAULT	PI_LDL_AP_S_NGS_005LUP	FN:6	PRODUCER	05-Mar-2002 20:24
REDUCE	PI_LDL_AP_S_NGS_005LUP	FN:7	PRODUCER	05-Mar-2002 20:24

## Output DLIS Files


DEFAULT	PI_LDL_AP_S_NGS_006LUP	FN:8	PRODUCER	05-Mar-2002 21:13	475.5 M	321.1 M
REDUCE	PI_LDL_AP_S_NGS_006LUP	FN:9	PRODUCER	05-Mar-2002 21:13	475.5 M	321.1 M



OP System Version: 10C0-306  
MCM



DIT-E	10C0-306	HLDT-A	10C0-306
DTA-A	10C0-306	NPLC-B	10C0-306
APS-BA	10C0-306	HNGS-BA	10C0-306
SGT-N	10C0-306	DTC-H	10C0-306


## PIP SUMMARY

Time Mark Every 60 S









### PIP SUMMARY

Time Mark Every 60 S

## Parameters

DLIS Name	Description	Value
BHS	DIT-E: Dual Induction - E	
GCSE	Borehole Status	OPEN
	Generalized Caliper Selection	CALI
BHS	APS-BA: Accelerator-Porosity Tool	
GCSE	Borehole Status	OPEN
	Generalized Caliper Selection	CALI
BAR1	HNGS-BA: Hostile Natural Gamma Ray Sonde	
BAR2	HNGS Detector 1 Barite Constant	1
BHK	HNGS Detector 2 Barite Constant	1
BHS	HNGS Borehole Potassium Correction Concentration	0
CSD1	Borehole Status	OPEN
CSD2	Inner Casing Outer Diameter	0
CSW1	Outer Casing Outer Diameter	0
CSW2	Inner Casing Weight	IN
	Outer Casing Weight	LB/F
DBCC	HNGS Barite Constant Correction Flag	NONE
GCSE	Generalized Caliper Selection	CALI
H1P	HNGS Detector 1 Allow/Disallow In Processing	ALLOW
H2P	HNGS Detector 2 Allow/Disallow In Processing	ALLOW
HABK	HNGS Borehole Potassium Running Average	-0.00262782
HALF	HNGS Alpha Filter Length	60
HCRB	HNGS Apply Borehole Potassium Correction	IN
HMWM	Mud Weighting Material	NATU
HNPE	HNGS Processing Enable	YES
S1BI	HNGS Detector 1 Calibration Bismuth Count Rate	1.3
S2BI	HNGS Detector 2 Calibration Bismuth Count Rate	CPS
SGRC	HNGS Standard Gamma-Ray Correction Flag	1.3
TPOS	Tool Position	YES
VBA1	HNGS Detector 1 Variable Barite Factor Running Average	ECCE
VBA2	HNGS Detector 2 Variable Barite Factor Running Average	0.963907
	SGT-N: Scintillation Gamma-Ray - N	0.979587
BHS	Borehole Status	OPEN
GCSE	Generalized Caliper Selection	CALI
BHS	HOLEV: Integrated Hole/Cement Volume	
GCSE	Borehole Status	OPEN
	Generalized Caliper Selection	CALI
BS	System and Miscellaneous	
DFD	Bit Size	11.438
	Drilling Fluid Density	IN
		1.07 G/C3

Format: HNGSYields Vertical Scale: 1:200 Graphics File Created: 05-Mar-2002 21:13

## OP System Version: 10C0-306 MCM

DIT-E	10C0-306	HLDT-A	10C0-306
DTA-A	10C0-306	NPLC-B	10C0-306
APS-BA	10C0-306	HNGS-BA	10C0-306
SGT-N	10C0-306	DTC-H	10C0-306

## Output DLIS Files

DEFAULT	PI_LDL_APSS_NGS_006LUP	FN:8	PRODUCER	05-Mar-2002 21:13
REDUCE	PI_LDL_APSS_NGS_006LUP	FN:9	PRODUCER	05-Mar-2002 21:13

Calibration and Check Summary							
Measurement	Nominal	Master	Before	After	Change	Limit	Units
<b>Hostile Environment Litho Density - A Wellsite Calibration - Background Measurement</b>							
Master: 25-Jan-2002 14:22 Before: 21-Feb-2002 4:36 After: 5-Mar-2002 22:52							
LSW1 Background	100.0	89.06	86.19	87.32	1.128	0.03000	CPS
LSW2 Background	105.0	93.23	91.94	90.71	-1.232	0.03000	CPS
LSW3 Background	210.0	180.0	177.0	178.4	1.437	0.03000	CPS
LSW4 Background	290.0	237.9	235.4	238.9	3.481	0.03000	CPS
LSW5 Background	610.0	529.6	525.7	522.6	-3.155	0.03000	CPS
SSW1 Background	100.0	85.18	85.99	84.17	-1.819	0.03000	CPS
SSW2 Background	200.0	166.8	165.6	166.6	1.022	0.03000	CPS
SSW3 Background	530.0	446.5	445.9	443.9	-1.961	0.03000	CPS
SSW4 Background	280.0	235.8	234.2	234.2	-0.04904	0.03000	CPS
SSW5 Background	205.0	176.3	175.5	177.2	1.732	0.03000	CPS
<b>Hostile Environment Litho Density - A Wellsite Calibration - Tool Quality Control Information High Voltage</b>							
Master: 25-Jan-2002 14:22 Before: 21-Feb-2002 4:36 After: 5-Mar-2002 22:52							
LS Bkg. High Voltage	1129	1129	1134	1134	0.3507	N/A	V
SS Bkg. High Voltage	1173	1173	1180	1176	-4.078	N/A	V
<b>Hostile Environment Litho Density - A Wellsite Calibration - Detectors Resolution From BKG Measurements</b>							
Master: 25-Jan-2002 14:22 Before: 21-Feb-2002 4:36 After: 5-Mar-2002 22:52							
LS Background Resolution	1.000	1.042	1.032	1.021	-0.01052	N/A	
SS Background Resolution	1.000	0.9530	0.9479	0.9514	0.003475	N/A	
<b>Hostile Environment Litho Density - A Wellsite Calibration - Caliper Calibration</b>							
Before: 7-Feb-2002 1:47							
Caliper Small Ring	12.00	N/A	16.99	N/A	N/A	N/A	IN
Caliper Large Ring	18.25	N/A	23.87	N/A	N/A	N/A	IN
<b>Accelerator-Porosity Tool Wellsite Calibration - Detector Background</b>							
Master: 25-Jan-2002 18:34 Before: 5-Mar-2002 19:53 After: 5-Mar-2002 22:19							
Near Det Bkg Cntrate	30.00	32.90	32.48	32.32	-0.1662	N/A	CPS
Far Det Bkg Cntrate	30.00	34.46	31.71	32.11	0.3989	N/A	CPS
Array-1 Det Bkg Cntrate	30.00	28.56	29.28	28.74	-0.5316	N/A	CPS
Array-2 Det Bkg Cntrate	30.00	30.78	31.29	30.35	-0.9304	N/A	CPS
Array Therm Det Bkg Cntrate	30.00	32.89	32.92	31.26	-1.660	N/A	CPS
<b>Accelerator-Porosity Tool Wellsite Calibration - Calibration Ratios</b>							
Master: 25-Jan-2002 18:35							
Near/Far Calibration Ratio	0.9250	0.9022	N/A	N/A	N/A	N/A	
Near/Array Calibration Ratio	1.030	1.063	N/A	N/A	N/A	N/A	
Near/Array Cal Ratio Up/Down	1.000	1.007	N/A	N/A	N/A	N/A	
<b>Accelerator-Porosity Tool Wellsite Calibration - Tank Check</b>							
Master: Calibration not done							
Array-1 Standoff Porosity	11.10	11.94	N/A	N/A	N/A	N/A	PU
Array-2 Standoff Porosity	11.10	11.71	N/A	N/A	N/A	N/A	PU
Average Slowing Down Time	6.000	N/A	N/A	N/A	N/A	N/A	US
Array-1 SDT Ratio Up/Down	1.000	N/A	N/A	N/A	N/A	N/A	
Array-1 SDT Ratio Up/Down	1.000	N/A	N/A	N/A	N/A	N/A	
Sigma Formation	27.50	27.64	N/A	N/A	N/A	N/A	CU
<b>Hostile Natural Gamma Ray Sonde Wellsite Calibration - Detector 1 Check</b>							
Master: 23-Jan-2002 11:37 Before: 7-Feb-2002 1:13 After: 5-Mar-2002 22:53							
Na 511 Peak Loc	40.00	40.51	40.71	40.51	-0.2026	1.000	
Na 511 Peak Res	15.50	15.75	17.24	16.07	-1.169	2.000	%
High Voltage	1150	1203	1207	1210	3.297	30.00	V
Na 1785 Peak Loc	142.6	144.6	146.2	145.4	-0.7214	7.000	
Na 1785 Peak Res	8.500	9.254	9.073	8.952	-0.1212	2.000	%
Temperature	15.50	21.86	29.34	28.14	-1.196	N/A	DEGC
Na Count Rate	45.00	39.29	40.56	39.01	-1.546	8.000	CPS
<b>Hostile Natural Gamma Ray Sonde Wellsite Calibration - Detector 2 Check</b>							
Master: 23-Jan-2002 11:37 Before: 7-Feb-2002 1:13 After: 5-Mar-2002 22:53							
Na 511 Peak Loc	40.00	40.54	40.54	40.62	0.07781	1.000	
Na 511 Peak Res	15.50	16.19	16.67	16.15	-0.5155	2.000	%
High Voltage	1150	1233	1236	1241	4.828	30.00	V
Na 1785 Peak Loc	142.6	143.9	144.1	145.5	1.374	7.000	
Na 1785 Peak Res	8.500	9.453	8.968	8.528	-0.4398	2.000	%
Temperature	15.50	21.24	29.04	28.42	-0.6178	N/A	DEGC
Na Count Rate	45.00	39.11	40.36	38.66	-1.698	8.000	CPS

## Hostile Natural Gamma Ray Sonde Wellsite Calibration - Ratio Of Detector 1 To Detector 2

Master: 23-Jan-2002 11:37 Before: 7-Feb-2002 1:13 After: 5-Mar-2002 22:53

Coincidence Count Rate Ratio 1.000 1.004 1.005 1.006 0.001129 0.05000

## Hostile Natural Gamma Ray Sonde Master Calibration - Detector 1 Calibration

Master: 23-Jan-2002 11:31

Na 511 Peak Set Point	40.00	41.00	--	--	--	--	
Th Peak Loc	209.6	209.7	--	--	--	--	
Th Peak Res	7.000	7.364	--	--	--	--	%
Background Count Rate	142.5	19.66	--	--	--	--	CPS
Gain Ratio	1.000	0.9848	--	--	--	--	

## Hostile Natural Gamma Ray Sonde Master Calibration - Detector 2 Calibration

Master: 23-Jan-2002 11:31

Na 511 Peak Set Point	40.00	41.00	--	--	--	--	
Th Peak Loc	209.6	208.7	--	--	--	--	
Th Peak Res	7.000	7.834	--	--	--	--	%
Background Count Rate	142.5	17.61	--	--	--	--	CPS
Gain Ratio	1.000	0.9795	--	--	--	--	

## Scintillation Gamma-Ray - N Wellsite Calibration - Detector Calibration

Before: 7-Feb-2002 1:09 After: Calibration not done

Gamma Ray (Jig - Bkg)	167.5	N/A	167.5	N/A	N/A	0.09091	GAPI
Gamma Ray (Calibrated)	165.0	N/A	165.0	N/A	N/A	15.00	GAPI

## Accelerator-Porosity Tool - Detector Plateau Settings :

Near Detector Plateau Setting 1748 V  
 Far Detector Plateau Setting 2052 V  
 Array Detector Plateau Setting 1969 V

## Dual Induction - E / Equipment Identification

Primary Equipment:				
Dual Induction Sonde		DIS - HB	442	
Dual Induction Cartridge		DIC - EB	438	
Auxiliary Equipment:				
Mass Isolated Housing		MIH - ZA	417	

## Hostile Environment Litho Density - A / Equipment Identification

Primary Equipment:				
HOSTILE ENVIRONMENT LITHO DENSITY HIGH V		HLDV - A	10	
HOSTILE ENVIRONMENT LITHO DENSITY CARTRI		HLDC - AA	11	
Gamma Source Radioactive		GSR - Z	1846	
Auxiliary Equipment:				
HOSTILE ENVIRONMENT LITHO DENSITY SONDE		HLDS - B	10	
HOSTILE ENVIRONMENT ELECTRONICS CARTRIDG		HEH - H	12	
HOSTILE ENVIRONMENT ELECTRONICS CARTRIDG		HEH - G	11	
HOSTILE ENVIRONMENT LITHO DENSITY PAD		HLDP - B	10	

## Nuclear Porosity Lithology Cartridge - B / Equipment Identification

Primary Equipment:				
NPLC Cartridge		NPLC - B	79	
Auxiliary Equipment:				
NPLC Housing		NPH - B	82	

## Accelerator-Porosity Tool / Equipment Identification

Primary Equipment:				
Accelerator-Porosity Sonde		APS - BA	22	
APS Minitron		MNTR - F	4185	

Auxiliary Equipment:  
 Accelerator-Porosity Housing  
 APS Calibration Water Tank  
 APS Aluminium Calibrator Sleeve

APH - AC 22  
 SFT - 178 4722  
 SFT - 281 24

### Hostile Natural Gamma Ray Sonde / Equipment Identification

Primary Equipment:  
 HNGS Sonde

HNGS - BA 77

Auxiliary Equipment:  
 HNGS Sonde Housing  
 Gamma Source Radioactive

HNSH - BA 79  
 GSR - U 135

### Hostile Natural Gamma Ray Sonde Wellsite Calibration

#### Detector 1 Check

Phase	Na 511 Peak Loc	Value	Phase	Na 511 Peak Res %	Value	Phase	High Voltage V	Value			
Master		40.51	Master		15.75	Master		1203			
Before		40.71	Before		17.24	Before		1207			
After		40.51	After		16.07	After		1210			
37.50 (Minimum) 40.00 (Nominal) 42.50 (Maximum)			12.00 (Minimum) 15.50 (Nominal) 19.00 (Maximum)			900.0 (Minimum) 1150 (Nominal) 1600 (Maximum)					
Phase	Na 1785 Peak Loc	Value	Phase	Na 1785 Peak Res %	Value	Phase	Temperature DEGC	Value			
Master		144.6	Master		9.254	Master		21.86			
Before		146.2	Before		9.073	Before		29.34			
After		145.4	After		8.952	After		28.14			
135.0 (Minimum) 142.6 (Nominal) 150.3 (Maximum)			7.000 (Minimum) 8.500 (Nominal) 11.00 (Maximum)			-28.89 (Minimum) 15.50 (Nominal) 60.00 (Maximum)					
Phase	Na Count Rate CPS	Value									
Master		39.29									
Before		40.56									
After		39.01									
15.00 (Minimum) 45.00 (Nominal) 100.0 (Maximum)											

Master: 23-Jan-2002 11:37

Before: 7-Feb-2002 1:13

After: 5-Mar-2002 22:53

### Hostile Natural Gamma Ray Sonde Wellsite Calibration

#### Detector 2 Check

Phase	Na 511 Peak Loc	Value	Phase	Na 511 Peak Res %	Value	Phase	High Voltage V	Value			
Master		40.54	Master		16.19	Master		1233			
Before		40.54	Before		16.67	Before		1236			
After		40.62	After		16.15	After		1241			
37.50 (Minimum) 40.00 (Nominal) 42.50 (Maximum)			12.00 (Minimum) 15.50 (Nominal) 19.00 (Maximum)			900.0 (Minimum) 1150 (Nominal) 1600 (Maximum)					
Phase	Na 1785 Peak Loc	Value	Phase	Na 1785 Peak Res %	Value	Phase	Temperature DEGC	Value			
Master		143.9	Master		9.453	Master		21.24			
Before		144.1	Before		8.968	Before		29.04			
After		145.5	After		8.528	After		28.42			
135.0 (Minimum) 142.6 (Nominal) 150.3 (Maximum)			7.000 (Minimum) 8.500 (Nominal) 11.00 (Maximum)			-28.89 (Minimum) 15.50 (Nominal) 60.00 (Maximum)					
Phase	Na Count Rate CPS	Value									
Master		39.11									
Before		40.36									
After		38.66									
15.00 (Minimum) 45.00 (Nominal) 100.0 (Maximum)											

Master: 23-Jan-2002 11:37

Before: 7-Feb-2002 1:13

After: 5-Mar-2002 22:53

Hostile Natural Gamma Ray Sonde Website Calibration			
Ratio Of Detector 1 To Detector 2			
Phase	Coincidence Count Rate Ratio	Value	
Master		1.004	
Before		1.005	
After		1.006	
	0.9500 (Minimum)	1.000 (Nominal)	1.050 (Maximum)

Master: 23-Jan-2002 11:37  
Before: 7-Feb-2002 1:13  
After: 5-Mar-2002 22:53

Hostile Natural Gamma Ray Sonde Master Calibration														
Detector 1 Calibration														
Phase	Na 511 Peak Set Point			Value	Phase	Th Peak Loc			Value	Phase	Th Peak Res %			Value
Master		41.00			Master		209.7			Master		7.364		
	38.00 (Minimum)	40.00 (Nominal)	42.00 (Maximum)			201.0 (Minimum)	209.6 (Nominal)	218.3 (Maximum)			5.000 (Minimum)	7.000 (Nominal)	9.000 (Maximum)	
Phase	Background Count Rate CPS			Value	Phase	Gain Ratio			Value					
Master	<span style="background-color: red; border: 1px solid black; padding: 2px;">EXCEEDS LIMIT</span>			19.66	Master		0.9848							
	20.00 (Minimum)	142.5 (Nominal)	265.0 (Maximum)			0.9400 (Minimum)	1.000 (Nominal)	1.060 (Maximum)						

Master: 23-Jan-2002 11:31

### See Remarks

Hostile Natural Gamma Ray Sonde Master Calibration														
Detector 2 Calibration														
Phase	Na 511 Peak Set Point			Value	Phase	Th Peak Loc			Value	Phase	Th Peak Res %			Value
Master		41.00			Master		208.7			Master		7.834		
	38.00 (Minimum)	40.00 (Nominal)	42.00 (Maximum)			201.0 (Minimum)	209.6 (Nominal)	218.3 (Maximum)			5.000 (Minimum)	7.000 (Nominal)	9.000 (Maximum)	
Phase	Background Count Rate CPS			Value	Phase	Gain Ratio			Value					
Master	<span style="background-color: red; border: 1px solid black; padding: 2px;">EXCEEDS LIMIT</span>			17.61	Master		0.9795							
	20.00 (Minimum)	142.5 (Nominal)	265.0 (Maximum)			0.9400 (Minimum)	1.000 (Nominal)	1.060 (Maximum)						

Master: 23-Jan-2002 11:31

### See Remarks

Scintillation Gamma-Ray - N / Equipment Identification											
Primary Equipment:											
Scintillation Gamma Cartridge											SGC - TB
Scintillation Gamma Detector											SGD - TAA
Auxiliary Equipment:											
Scintillation Gamma Housing											SGH - K
Gamma Source Radioactive											GSR - U/Y

Company: Lamont Doherty

**Schlumberger**

Well: ODP Leg 201, Site 1228A PRU-2A  
 Field: Peru Margin  
 Rig: JOIDES Resolution  
 Ocean: Pacific

Natural Gamma Ray

# Spectroscopy (HNGS)