

Company: Lamont Doherty

Well: ODP Leg 209, Site 1272A

Field: Mid Atlantic Ridge

Country: Ocean: Atlantic

Phasor Induction Natural Gamma Ray

Country: Mid Atlantic Ridge
Field: Rig- Joides Resolution
Location: ODP Leg 209, Site 1272A
Well: ODP Leg 209, Site 1272A
Company: Lamont Doherty

LOCATION	
Rig- Joides Resolution	Elev.: K.B. 11.3 m
15 Deg 5.6682 ' N	G.L. -2571 m
44 Deg 58.2994 ' W	D.F. 11 m
Permanent Datum: _____	MSL _____
Log Measured From: _____	DES _____
Drilling Measured From: _____	DES _____
Elev.: 0 m	
11.3 m above Perm. Datum	

API Serial No. _____	Max. Hole Devi. _____	Longitude 91.9343 W	Latitude 6.7365 N
----------------------	-----------------------	---------------------	-------------------

Logging Date	11-Jun-2003
Run Number	1
Depth Driller	2702 m
Schlumberger Depth	2695 m
Bottom Log Interval	2693 m
Top Log Interval	2600 m
Casing Driller Size @ Depth	0.000 in @ 2612 m
Casing Schlumberger	2610 m
Bit Size	9.875 in

Type Fluid In Hole		Septolite	
Density	Viscosity	1.066 g/cm3	
Fluid Loss	PH		
Source Of Sample			
RM @ Measured Temperature	@	73 degC	@
RMF @ Measured Temperature	@		@
RMC @ Measured Temperature	@		@
Source RMF	RMC		
RM @ MRT	RMF @ MRT	0.945 @ 11	@ 11
Maximum Recorded Temperatures	11 degC		
Circulation Stopped	Time	11-Jun-2003	
Logger On Bottom	Time	11-Jun-2003	See Log
Unit Number	Location	99	Houston
Recorded By		K. Swain	
Witnessed By		G. Iturrino	

Logging Date	11-Jun-2003		
Run Number	1		
Depth Driller	2702 m		
Schlumberger Depth	2695 m		
Bottom Log Interval	2693 m		
Top Log Interval	2600 m		
Casing Driller Size @ Depth	0.000 in @ 2612 m		
Casing Schlumberger	2610 m		
Bit Size	9.875 in		
Type Fluid In Hole		Septolite	
Density	Viscosity	1.066 g/cm3	
Fluid Loss	PH		
Source Of Sample			
RM @ Measured Temperature	@	73 degC	@
RMF @ Measured Temperature	@		@
RMC @ Measured Temperature	@		@
Source RMF	RMC		
RM @ MRT	RMF @ MRT	0.945 @ 11	@ 11
Maximum Recorded Temperatures	11 degC		
Circulation Stopped	Time	11-Jun-2003	
Logger On Bottom	Time	11-Jun-2003	See Log
Unit Number	Location	99	Houston
Recorded By		K. Swain	
Witnessed By		G. Iturrino	

Logging Date	11-Jun-2003		
Run Number	1		
Depth Driller	2702 m		
Schlumberger Depth	2695 m		
Bottom Log Interval	2693 m		
Top Log Interval	2600 m		
Casing Driller Size @ Depth	0.000 in @ 2612 m		
Casing Schlumberger	2610 m		
Bit Size	9.875 in		
Type Fluid In Hole		Septolite	
Density	Viscosity	1.066 g/cm3	
Fluid Loss	PH		
Source Of Sample			
RM @ Measured Temperature	@	73 degC	@
RMF @ Measured Temperature	@		@
RMC @ Measured Temperature	@		@
Source RMF	RMC		
RM @ MRT	RMF @ MRT	0.945 @ 11	@ 11
Maximum Recorded Temperatures	11 degC		
Circulation Stopped	Time	11-Jun-2003	
Logger On Bottom	Time	11-Jun-2003	See Log
Unit Number	Location	99	Houston
Recorded By		K. Swain	
Witnessed By		G. Iturrino	

DISCLAIMER

THE USE OF AND RELIANCE UPON THIS RECORDED-DATA BY THE HEREIN NAMED COMPANY (AND ANY OF ITS AFFILIATES, PARTNERS, REPRESENTATIVES, AGENTS, CONSULTANTS AND EMPLOYEES) IS SUBJECT TO THE TERMS AND CONDITIONS AGREED UPON BETWEEN SCHLUMBERGER AND THE COMPANY, INCLUDING: (a) RESTRICTIONS ON USE OF THE RECORDED-DATA; (b) DISCLAIMERS AND WAIVERS OF WARRANTIES AND REPRESENTATIONS REGARDING COMPANY'S USE OF AND RELIANCE UPON THE RECORDED-DATA; AND (c) CUSTOMER'S FULL AND SOLE RESPONSIBILITY FOR ANY INFERENCE DRAWN OR DECISION MADE IN CONNECTION WITH THE USE OF THIS RECORDED-DATA.



OTHER SERVICES1 OS1: HLDS OS2: DSST OS3: FMS OS4: OS5:	OTHER SERVICES2 OS1: OS2: OS3: OS4: OS5:
---	---


REMARKS: RUN NUMBER 1 Hole cored with RCB 9 7/8" bit. All depths in Meters Below Rig Floor (MBRF). Sepiolite mud was used. WHC was run. See logging report for more information. 10khz and 40khz not used with DITE Low background countrate for HNGS does not affect measurement...indication of weak background sources only.	REMARKS: RUN NUMBER 2
--	-----------------------

RUN 1			RUN 2		
SERVICE ORDER #:			SERVICE ORDER #:		
PROGRAM VERSION:		10C0-306	PROGRAM VERSION:		
FLUID LEVEL:			FLUID LEVEL:		
LOGGED INTERVAL	START	STOP	LOGGED INTERVAL	START	STOP

EQUIPMENT DESCRIPTION

RUN 1		RUN 2	
SURFACE EQUIPMENT			
GSR-U 135 WITM (DTS)-A			

DOWNHOLE EQUIPMENT			
LEH-QT			22.31
LEH-QT			
DTC-H	CTEM TelStatus ToolStatu	— 21.14	21.42
ECH-KC 9343 DTCH0-A		— 20.51	
HNGS DA			20.51



MAXIMUM STRING DIAMETER 3.75 IN
 MEASUREMENTS RELATIVE TO TOOL ZERO
 ALL LENGTHS IN METERS

Output DLIS Files

DEFAULT	PI_LDL_NGS_006LUP	FN:6	PRODUCER	11-Jun-2003 18:23	2695.2 M	2550.1 M
REDUCED	PI_LDL_NGS_006LUP	FN:7	PRODUCER	11-Jun-2003 18:23	2695.2 M	2550.1 M

OP System Version: 10C0-306

MCM


DIT-E	10C0-306	DTA-A	10C0-306
HLDS	SPC-2277-NUCL_b	NPLC-B	OP10-KP1
HNGS-BA	SPC-2277-NUCL_b	DTC-H	10C0-306


Changed Parameter Summary


DLIS Name	New Value	Previous Value	Depth & Time
GCSE	BS LCAL	BS BS	2692.0 18:25:08 2691.1 18:25:18

PIP SUMMARY

Time Mark Every 60 S








-Drill Pipe-

-Caliper Closed

2625

2650



<p>HLDS Caliper (LCAL) (IN)</p> <p>0 20</p>	<p>Tension (TENS) (LBF)</p> <p>10000 0</p>	<p>Deep Induction Phasor-processed Resistivity (IDPH) (OHMM)</p> <p>0.2 2000</p>
<p>HNGS Spectroscopy Gamma Ray (HSGR) (GAPI)</p> <p>0 150</p>	<p>ID_QUAL From IMQF to IDQF</p>	<p>Medium Induction Phasor-processed Resistivity (IMPH) (OHMM)</p> <p>0.2 2000</p>
	<p>IM_QUAL From SFQF to IMQF</p>	<p>SFL Unaveraged (SFLU) (OHMM)</p> <p>0.2 2000</p>
	<p>SFL_QUAL From D3T to SFQF</p>	<p>Main Log</p>

PIP SUMMARY

▶ Time Mark Every 60 S

Parameters

DLIS Name	Description	Value
-----------	-------------	-------

DIT-E: Dual Induction - E

BHS	Borehole Status	OPEN	
BHT	Bottom Hole Temperature (used in calculations)	15	DEGC
DGF2	Deep 20 kHz Gain Factor	1.00789	
DPH2	Deep 20 kHz Phase Shift	-0.152394	DEG
DRE2	Deep Real 20 kHz Sonde Error Correction	16.357	MM/M
DSR2	Deep Sigma Reference (20 kHz)	1843	MM/M
DXE2	Deep Quad 20 kHz Sonde Error Correction	64.6326	MM/M
GCSE	Generalized Caliper Selection	BS	
GDEV	Average Angular Deviation of Borehole from Normal	0	DEG
GGRD	Geothermal Gradient	0.018227	DC/M
GTSE	Generalized Temperature Selection	LINEAR_ESTIMATE	
IFRS	DIT-E Induction Frequency Selector	20	
IPHA	DIT-E Phasor Processing Mode	ALL	
IPRO	DIT-E Induction Processing Selector	PHASOR	
ITEN	DIT-E Temperature Enable	ENABLE	
MGF2	Medium 20 kHz Gain Factor	1.02964	
MPH2	Medium 20 kHz Phase Shift	-0.933067	DEG
MRE2	Medium Real 20 kHz Sonde Error Correction	-1.78642	MM/M
MSR2	Medium Sigma Reference (20 kHz)	3250	MM/M
MXE2	Medium Quad 20 kHz Sonde Error Correction	-34.2041	MM/M
SFCR	SFL Channel Ratio	1000	
SHT	Surface Hole Temperature	20	DEGC

HNGS-BA: Hostile Natural

BAR1	HNGS Detector 1 Barite Constant	1	
BAR2	HNGS Detector 2 Barite Constant	1	
BHK	HNGS Borehole Potassium Correction Concentration	0	
BHS	Borehole Status	OPEN	
BHT	Bottom Hole Temperature (used in calculations)	15	DEGC
CSD1	Inner Casing Outer Diameter	0	IN
CSD2	Outer Casing Outer Diameter	0	IN
CSW1	Inner Casing Weight	0	LB/F
CSW2	Outer Casing Weight	0	LB/F
DBCC	HNGS Barite Constant Correction Flag	NONE	
GCSE	Generalized Caliper Selection	BS	
GDEV	Average Angular Deviation of Borehole from Normal	0	DEG
GGRD	Geothermal Gradient	0.018227	DC/M
GTSE	Generalized Temperature Selection	LINEAR_ESTIMATE	
H1P	HNGS Detector 1 Allow/Disallow In Processing	ALLOW	
H2P	HNGS Detector 2 Allow/Disallow In Processing	ALLOW	
HABK	HNGS Borehole Potassium Running Average	-0.00262528	
HALF	HNGS Alpha Filter Length	60	IN
HCRB	HNGS Apply Borehole Potassium Correction	NONE	
HMWM	Mud Weighting Material	NATU	
HNPE	HNGS Processing Enable	YES	
S1BI	HNGS Detector 1 Calibration Bismuth Count Rate	1.3	CPS
S2BI	HNGS Detector 2 Calibration Bismuth Count Rate	1.3	CPS
SGRC	HNGS Standard Gamma-Ray Correction Flag	YES	
SHT	Surface Hole Temperature	20	DEGC
TPOS	Tool Position	ECCE	
VBA1	HNGS Detector 1 Variable Barite Factor Running Average	1.4421	
VBA2	HNGS Detector 2 Variable Barite Factor Running Average	3.72744	

System and Miscellaneous

BS	Bit Size	9.875	IN
DFD	Drilling Fluid Density	1.07	G/C3
TD	Total Depth	2710	M

Format: DITE_LogPhasor Vertical Scale: 1:200 Graphics File Created: 11-Jun-2003 18:23

OP System Version: 10C0-306
MCM

DIT-E	10C0-306	DTA-A	10C0-306
HLDS	SPC-2277-NUCL_b	NPLC-B	OP10-KP1
HNGS-BA	SPC-2277-NUCL_b	DTC-H	10C0-306

Output DLIS Files

DEFAULT	PI_LDL_NGS_006LUP	FN:6	PRODUCER	11-Jun-2003 18:23
REDUCED	PI_LDL_NGS_006LUP	FN:7	PRODUCER	11-Jun-2003 18:23

Output DLIS Files


DEFAULT	PI_LDL_NGS_007LUP	FN:8	PRODUCER	11-Jun-2003 18:51	2695.2 M	2592.3 M
REDUCED	PI_LDL_NGS_007LUP	FN:9	PRODUCER	11-Jun-2003 18:51	2695.2 M	2591.0 M


OP System Version: 10C0-306
MCM



PIP SUMMARY

Time Mark Every 60 S

	SFL_QUAL From D3T to SFQF	
	IM_QUAL From SFQF to IMQF	SFL Unaveraged (SFLU) (OHMM)
HNGS Spectroscopy Gamma Ray (HSGR) (GAPI)	ID_QUAL From IMQF to IDQF	Medium Induction Phasor-processed Resistivity (IMPH) (OHMM)
HLDS Caliper (LCAL) (IN)	Tension (TENS) (LBF)	Deep Induction Phasor-processed Resistivity (IDPH) (OHMM)







PIP SUMMARY

Time Mark Every 60 S

Parameters

DLIS Name	Description	Value
DIT-E: Dual Induction - E		
BHS	Borehole Status	OPEN
BHT	Bottom Hole Temperature (used in calculations)	15 DEGC
DGF2	Deep 20 kHz Gain Factor	1.00789
DPH2	Deep 20 kHz Phase Shift	-0.152394 DEG
DRE2	Deep Real 20 kHz Sonde Error Correction	16.357 MM/M
DSR2	Deep Sigma Reference (20 kHz)	1843 MM/M
DXE2	Deep Quad 20 kHz Sonde Error Correction	64.6326 MM/M
GCSE	Generalized Caliper Selection	LCAL
GDEV	Average Angular Deviation of Borehole from Normal	0 DEG
GGRD	Geothermal Gradient	0.018227 DC/M
GTSE	Generalized Temperature Selection	LINEAR_ESTIMATE
IFRS	DIT-E Induction Frequency Selector	20
IPHA	DIT-E Phasor Processing Mode	ALL
IPRO	DIT-E Induction Processing Selector	PHASOR
ITEN	DIT-E Temperature Enable	ENABLE
MGF2	Medium 20 kHz Gain Factor	1.02964
MPH2	Medium 20 kHz Phase Shift	-0.933067 DEG
MRE2	Medium Real 20 kHz Sonde Error Correction	-1.78642 MM/M
MSR2	Medium Sigma Reference (20 kHz)	3250 MM/M
MXE2	Medium Quad 20 kHz Sonde Error Correction	-34.2041 MM/M
SFCR	SFL Channel Ratio	1000
SHT	Surface Hole Temperature	20 DEGC
HNGS-BA: Hostile Natural Gamma Ray Sonde		
BAR1	HNGS Detector 1 Barite Constant	1
BAR2	HNGS Detector 2 Barite Constant	1
BHK	HNGS Borehole Potassium Correction Concentration	0
BHS	Borehole Status	OPEN
BHT	Bottom Hole Temperature (used in calculations)	15 DEGC
CSD1	Inner Casing Outer Diameter	0 IN
CSD2	Outer Casing Outer Diameter	0 IN

CSW1	Cuttings Weight	0	LB/F
CSW2	Outer Casing Weight	0	LB/F
DBCC	HNGS Barite Constant Correction Flag	NONE	
GCSE	Generalized Caliper Selection	LCAL	
GDEV	Average Angular Deviation of Borehole from Normal	0	DEG
GGRD	Geothermal Gradient	0.018227	DC/M
GTSE	Generalized Temperature Selection	LINEAR_ESTIMATE	
H1P	HNGS Detector 1 Allow/Disallow In Processing	ALLOW	
H2P	HNGS Detector 2 Allow/Disallow In Processing	ALLOW	
HABK	HNGS Borehole Potassium Running Average	-0.00443434	
HALF	HNGS Alpha Filter Length	60	IN
HCRB	HNGS Apply Borehole Potassium Correction	NONE	
HMWM	Mud Weighting Material	NATU	
HNPE	HNGS Processing Enable	YES	
S1BI	HNGS Detector 1 Calibration Bismuth Count Rate	1.3	CPS
S2BI	HNGS Detector 2 Calibration Bismuth Count Rate	1.3	CPS
SGRC	HNGS Standard Gamma-Ray Correction Flag	YES	
SHT	Surface Hole Temperature	20	DEGC
TPOS	Tool Position	ECCE	
VBA1	HNGS Detector 1 Variable Barite Factor Running Average	1.09098	
VBA2	HNGS Detector 2 Variable Barite Factor Running Average	1.38912	
System and Miscellaneous			
BS	Bit Size	9.875	IN
DFD	Drilling Fluid Density	1.07	G/C3
TD	Total Depth	2710	M

Format: DITE_LogPhasor Vertical Scale: 1:200 Graphics File Created: 11-Jun-2003 18:51

OP System Version: 10C0-306

MCM

DIT-E	10C0-306	DTA-A	10C0-306
HLDS	SPC-2277-NUCL_b	NPLC-B	OP10-KP1
HNGS-BA	SPC-2277-NUCL_b	DTC-H	10C0-306

Output DLIS Files

DEFAULT	PI_LDL_NGS_007LUP	FN:8	PRODUCER	11-Jun-2003 18:51
REDUCED	PI_LDL_NGS_007LUP	FN:9	PRODUCER	11-Jun-2003 18:51

Calibration and Check Summary

Measurement	Nominal	Master	Before	After	Change	Limit	Units
Hostile Litho-Density Sonde Wellsite Calibration - Background Measurement							
Master: 23-Apr-2003 17:32 Before: 18-May-2003 20:52 After: 11-Jun-2003 21:44							
SS Cs Resolution Bkg	9.000	8.094	8.097	8.005	-0.09238	1.800	%
LS Cs Resolution Bkg	9.000	8.143	8.212	8.247	0.03477	1.800	%
LSW1 Background	100.0	86.47	86.14	86.02	-0.1230	0.03000	CPS
LSW2 Background	100.0	80.63	80.44	80.53	0.09354	0.03000	CPS
LSW3 Background	200.0	177.7	178.3	177.1	-1.207	0.03000	CPS
LSW4 Background	250.0	218.9	217.1	218.1	0.9930	0.03000	CPS
LSW5 Background	600.0	499.0	499.9	499.6	-0.3034	0.03000	CPS
SSW1 Background	100.0	97.29	95.44	95.90	0.4648	0.03000	CPS
SSW2 Background	200.0	175.4	174.0	174.0	-0.01474	0.03000	CPS
SSW3 Background	500.0	475.0	475.2	472.2	-3.004	0.03000	CPS
SSW4 Background	270.0	242.4	242.8	241.6	-1.130	0.03000	CPS
SSW5 Background	200.0	176.0	175.7	174.9	-0.7180	0.03000	CPS
Hostile Litho-Density Sonde Wellsite Calibration - Aluminum Measurement							
Master: 23-Apr-2003 18:33							
LSW1 Aluminum	600.0	604.1	N/A	N/A	N/A	N/A	CPS
LSW2 Aluminum	900.0	860.3	N/A	N/A	N/A	N/A	CPS
LSW3 Aluminum	1100	1017	N/A	N/A	N/A	N/A	CPS
LSW4 Aluminum	580.0	498.2	N/A	N/A	N/A	N/A	CPS
LSW5 Aluminum	570.0	473.1	N/A	N/A	N/A	N/A	CPS
SSW1 Aluminum	2800	2618	N/A	N/A	N/A	N/A	CPS
SSW2 Aluminum	8000	7129	N/A	N/A	N/A	N/A	CPS
SSW3 Aluminum	11600	9926	N/A	N/A	N/A	N/A	CPS
SSW4 Aluminum	5000	4181	N/A	N/A	N/A	N/A	CPS
SSW5 Aluminum	660.0	547.6	N/A	N/A	N/A	N/A	CPS
Hostile Litho-Density Sonde Wellsite Calibration - Lithology Measurement							
Master: 23-Apr-2003 18:29							
LSW1 Iron	400.0	418.2	N/A	N/A	N/A	N/A	CPS

LSW2 Iron	730.0	721.5	N/A	N/A	N/A	N/A	N/A	CPS
LSW3 Iron	1000	941.8	N/A	N/A	N/A	N/A	N/A	CPS
LSW4 Iron	520.0	481.5	N/A	N/A	N/A	N/A	N/A	CPS
LSW5 Iron	470.0	449.9	N/A	N/A	N/A	N/A	N/A	CPS
SSW1 Iron	2100	1956	N/A	N/A	N/A	N/A	N/A	CPS
SSW2 Iron	6800	6092	N/A	N/A	N/A	N/A	N/A	CPS
SSW3 Iron	10800	9264	N/A	N/A	N/A	N/A	N/A	CPS
SSW4 Iron	4600	3922	N/A	N/A	N/A	N/A	N/A	CPS
SSW5 Iron	580.0	501.5	N/A	N/A	N/A	N/A	N/A	CPS

Hostile Litho-Density Sonde Wellsite Calibration - Caliper Calibration

Before: 18-May-2003 20:24

HLDS Caliper Small Ring	12.00	N/A	14.48	N/A	N/A	N/A	IN
HLDS Caliper Large Ring	15.00	N/A	17.56	N/A	N/A	N/A	IN

Hostile Natural Gamma Ray Sonde Wellsite Calibration - Detector 1 Check

Master: 10-Jun-2003 9:13 Before: 8-Apr-2003 2:33 After: 11-Jun-2003 21:45

Na 511 Peak Loc	40.00	40.65	40.63	40.56	-0.07085	1.000	
Na 511 Peak Res	15.50	16.98	16.69	16.31	-0.3779	2.000	%
High Voltage	1150	1208	1207	1208	0.6575	30.00	V
Na 1785 Peak Loc	142.6	145.2	145.2	144.9	-0.2784	7.000	
Na 1785 Peak Res	8.500	8.982	9.496	9.778	0.2824	2.000	%
Temperature	15.50	33.02	27.12	31.28	4.158	N/A	DEGC
Na Count Rate	45.00	40.11	41.75	39.73	-2.015	8.000	CPS

Hostile Natural Gamma Ray Sonde Wellsite Calibration - Detector 2 Check

Master: 10-Jun-2003 9:13 Before: 8-Apr-2003 2:33 After: 11-Jun-2003 21:45

Na 511 Peak Loc	40.00	40.56	40.51	40.64	0.1261	1.000	
Na 511 Peak Res	15.50	17.13	16.55	16.78	0.2294	2.000	%
High Voltage	1150	1234	1235	1234	-0.9994	30.00	V
Na 1785 Peak Loc	142.6	144.4	144.2	144.7	0.5310	7.000	
Na 1785 Peak Res	8.500	9.188	9.586	9.068	-0.5173	2.000	%
Temperature	15.50	32.54	26.30	31.70	5.397	N/A	DEGC
Na Count Rate	45.00	40.04	41.81	39.37	-2.441	8.000	CPS

Hostile Natural Gamma Ray Sonde Wellsite Calibration - Ratio Of Detector 1 To Detector 2

Master: 10-Jun-2003 9:13 Before: 8-Apr-2003 2:33 After: 11-Jun-2003 21:45

Coincidence Count Rate Ratio	1.000	1.001	0.9991	1.008	0.009050	0.05000	
------------------------------	-------	-------	--------	-------	----------	---------	--

Hostile Natural Gamma Ray Sonde Master Calibration - Detector 1 Calibration

Master: 10-Jun-2003 8:55

Na 511 Peak Set Point	40.00	41.00	--	--	--	--	
Th Peak Loc	209.6	209.0	--	--	--	--	
Th Peak Res	7.000	8.425	--	--	--	--	%
Background Count Rate	142.5	19.30	--	--	--	--	CPS
Gain Ratio	1.000	0.9783	--	--	--	--	

Hostile Natural Gamma Ray Sonde Master Calibration - Detector 2 Calibration

Master: 10-Jun-2003 8:55

Na 511 Peak Set Point	40.00	41.00	--	--	--	--	
Th Peak Loc	209.6	209.4	--	--	--	--	
Th Peak Res	7.000	8.230	--	--	--	--	%
Background Count Rate	142.5	18.75	--	--	--	--	CPS
Gain Ratio	1.000	0.9823	--	--	--	--	

Dual Induction - E / Equipment Identification

Primary Equipment:

Dual Induction Sonde	DIS - HB	442
Dual Induction Cartridge	DIC - EB	438

Auxiliary Equipment:

Mass Isolated Housing	MIH - ZA	
-----------------------	----------	--

Dual Induction - E Wellsite Calibration

Induction Electronics (10 kHz)

Phase	ID Elect Real Offset 10 kHz MM/M	Value	Phase	ID Elect Real Gain 10 kHz	Value	Phase	ID Elect Phase 10 kHz DEG	Value
Before		39.11	Before		1.008	Before		8.931
Phase	ID Elect Quad Offset 10 kHz MM/M	Value	Phase	ID Elect Quad Gain 10 kHz	Value	Phase	IM Elect Phase 10 kHz DEG	Value
Before		24.21	Before		0.9961	Before		13.46

10kHz not used

Phase	IM Elect Real Offset 10 kHz	MM/M	Value	Phase	IM Elect Real Gain 10 kHz	Value	
Before			97.65	Before		0.9505	
	-550.0 (Minimum)	0 (Nominal)	550.0 (Maximum)		0.8500 (Minimum)	1.000 (Nominal)	1.200 (Maximum)
Phase	IM Elect Quad Offset 10 kHz	MM/M	Value	Phase	IM Elect Quad Gain 10 kHz	Value	
Before			96.54	Before		0.9481	
	-550.0 (Minimum)	0 (Nominal)	550.0 (Maximum)		0.8500 (Minimum)	1.000 (Nominal)	1.200 (Maximum)

Before: 18-May-2003 20:19

Dual Induction - E Wellsite Calibration											
Induction Electronics (20 kHz)											
Phase	ID Elect Real Offset 20 kHz	MM/M	Value	Phase	ID Elect Real Gain 20 kHz	Value	Phase	ID Elect Phase 20 kHz	DEG	Value	
Before			15.17	Before		1.018	Before			7.778	
	-125.0 (Minimum)	0 (Nominal)	125.0 (Maximum)		0.8500 (Minimum)	1.000 (Nominal)	1.200 (Maximum)		-15.00 (Minimum)	0 (Nominal)	15.00 (Maximum)
Phase	ID Elect Quad Offset 20 kHz	MM/M	Value	Phase	ID Elect Quad Gain 20 kHz	Value	Phase	IM Elect Phase 20 kHz	DEG	Value	
Before			9.581	Before		1.006	Before			12.48	
	-125.0 (Minimum)	0 (Nominal)	125.0 (Maximum)		0.8500 (Minimum)	1.000 (Nominal)	1.200 (Maximum)		-15.00 (Minimum)	0 (Nominal)	15.00 (Maximum)
Phase	IM Elect Real Offset 20 kHz	MM/M	Value	Phase	IM Elect Real Gain 20 kHz	Value	40kHz not used				
Before			40.79	Before		1.011					
	-225.0 (Minimum)	0 (Nominal)	225.0 (Maximum)		0.8500 (Minimum)	1.000 (Nominal)					1.200 (Maximum)
Phase	IM Elect Quad Offset 20 kHz	MM/M	Value	Phase	IM Elect Quad Gain 20 kHz	Value					
Before			40.43	Before		1.009					
	-225.0 (Minimum)	0 (Nominal)	225.0 (Maximum)		0.8500 (Minimum)	1.000 (Nominal)	1.200 (Maximum)				

Before: 18-May-2003 20:20

Dual Induction - E Wellsite Calibration											
Induction Electronics (40 kHz)											
Phase	ID Elect Real Offset 40 kHz	MM/M	Value	Phase	ID Elect Real Gain 40 kHz	Value	Phase	ID Elect Phase 40 kHz	DEG	Value	
Before			9.909	Before		0.9935	Before		EXCEEDS LIMIT	28.32	
	-85.00 (Minimum)	0 (Nominal)	85.00 (Maximum)		0.8500 (Minimum)	1.000 (Nominal)	1.200 (Maximum)		-20.00 (Minimum)	0 (Nominal)	20.00 (Maximum)
Phase	ID Elect Quad Offset 40 kHz	MM/M	Value	Phase	ID Elect Quad Gain 40 kHz	Value	Phase	IM Elect Phase 40 kHz	DEG	Value	
Before			6.231	Before		0.9807	Before		EXCEEDS LIMIT	32.92	
	-85.00 (Minimum)	0 (Nominal)	85.00 (Maximum)		0.8500 (Minimum)	1.000 (Nominal)	1.200 (Maximum)		-20.00 (Minimum)	0 (Nominal)	20.00 (Maximum)
Phase	IM Elect Real Offset 40 kHz	MM/M	Value	Phase	IM Elect Real Gain 40 kHz	Value	40kHz not used				
Before			26.67	Before		1.026					
	-130.0 (Minimum)	0 (Nominal)	130.0 (Maximum)		0.8500 (Minimum)	1.000 (Nominal)					1.200 (Maximum)
Phase	IM Elect Quad Offset 40 kHz	MM/M	Value	Phase	IM Elect Quad Gain 40 kHz	Value					
Before			26.51	Before		1.023					
	-130.0 (Minimum)	0 (Nominal)	130.0 (Maximum)		0.8500 (Minimum)	1.000 (Nominal)	1.200 (Maximum)				

Before: 18-May-2003 20:21

Dual Induction - E Wellsite Calibration							
SFL Electronics							
Phase	SFL Voltage Offset	MV	Value	Phase	SFL Voltage Gain	Value	
Before			1.302	Before		1.020	
	-15.00 (Minimum)	0 (Nominal)	15.00 (Maximum)		0.8500 (Minimum)	1.000 (Nominal)	1.200 (Maximum)
Phase	SFL Current Offset	MA	Value	Phase	SFL Current Gain	Value	
Before			0.005040	Before		0.9969	
	-0.6000 (Minimum)	0 (Nominal)	0.6000 (Maximum)		0.8500 (Minimum)	1.000 (Nominal)	1.200 (Maximum)

Before: 18-May-2003 20:22

Dual Induction - E Wellsite Calibration											
Electronics Calibration Changes Files/Depth Intervals:											
Phase	ID (R > 27 OHM-M)	MM/M	Value	Phase	ID (R < 27 OHM-M)	%	Value	Phase	SFL (R < 1 OHM-M)	OHMM	Value

After		0	After		0.0002458	After		0
	0 (Minimum) 0 (Nominal) 0.7500 (Maximum)			0 (Minimum) 0 (Nominal) 2.000 (Maximum)			0 (Minimum) 0 (Nominal) 0.02000 (Maximum)	
Phase	IM (R > 27 OHM-M) MM/M	Value	Phase	IM (R < 27 OHM-M) %	Value			
After		0	After		0.0002466			
	0 (Minimum) 0 (Nominal) 0.7500 (Maximum)			0 (Minimum) 0 (Nominal) 2.000 (Maximum)				
Phase	SFL (R > 27 OHM-M) MM/M	Value	Phase	SFL (R < 27 OHM-M) %	Value			
After		0	After		0.0002716			
	0 (Minimum) 0 (Nominal) 0.7500 (Maximum)			0 (Minimum) 0 (Nominal) 2.000 (Maximum)				

After: 11-Jun-2003 20:17

Dual Induction - E Master Calibration								
Test Loop Calibration: Calibration of Internal Reference to Test Loop Standard								
Phase	Deep 10 kHz Gain Factor	Value	Phase	Deep 20 kHz Gain Factor	Value	Phase	Deep 40 kHz Gain Factor	Value
Master		0.9956	Master		1.008	Master		1.026
	0.9000 (Minimum) 1.000 (Nominal) 1.100 (Maximum)			0.9000 (Minimum) 1.000 (Nominal) 1.100 (Maximum)			0.9000 (Minimum) 1.000 (Nominal) 1.100 (Maximum)	
Phase	Medium 10 kHz Gain Factor	Value	Phase	Medium 20 kHz Gain Factor	Value	Phase	Medium 40 kHz Gain Factor	Value
Master		1.022	Master		1.030	Master		1.061
	0.9000 (Minimum) 1.000 (Nominal) 1.100 (Maximum)			0.9000 (Minimum) 1.000 (Nominal) 1.100 (Maximum)			0.9000 (Minimum) 1.000 (Nominal) 1.100 (Maximum)	
Phase	Deep 10 kHz Phase Shift	Value	Phase	Deep 20 kHz Phase Shift	Value	Phase	Deep 40 kHz Phase Shift	Value
Master		0.1143	Master		-0.1524	Master		-1.426
	-1.500 (Minimum) 0 (Nominal) 1.500 (Maximum)			-2.000 (Minimum) 0 (Nominal) 2.000 (Maximum)			-4.000 (Minimum) -1.000 (Nominal) 2.000 (Maximum)	
Phase	Medium 10 kHz Phase Shift	Value	Phase	Medium 20 kHz Phase Shift	Value	Phase	Medium 40 kHz Phase Shift	Value
Master		-0.2558	Master		-0.9331	Master		-2.461
	-1.500 (Minimum) 0 (Nominal) 1.500 (Maximum)			-3.000 (Minimum) -1.000 (Nominal) 1.000 (Maximum)			-5.000 (Minimum) -2.000 (Nominal) 1.000 (Maximum)	

Master: Calibration out of date 5-Oct-2001 19:50

Dual Induction - E Master Calibration								
Sonde Error Corrections: Correction for sonde response in zero conductivity environment. (Normalized to 25C).								
Phase	Real Deep 10 kHz S.E. Corr.	Value	Phase	Real Deep 20 kHz S.E. Corr.	Value	Phase	Real Deep 40 kHz S.E. Corr.	Value
Master		44.95	Master		16.36	Master		4.690
	-50.00 (Minimum) 0 (Nominal) 125.0 (Maximum)			-30.00 (Minimum) 0 (Nominal) 30.00 (Maximum)			-15.00 (Minimum) 0 (Nominal) 15.00 (Maximum)	
Phase	Quad Deep 10 kHz S.E. Corr.	Value	Phase	Quad Deep 20 kHz S.E. Corr.	Value	Phase	Quad Deep 40 kHz S.E. Corr.	Value
Master		108.9	Master		64.63	Master		46.10
	-250.0 (Minimum) 0 (Nominal) 350.0 (Maximum)			-125.0 (Minimum) 0 (Nominal) 200.0 (Maximum)			-75.00 (Minimum) 0 (Nominal) 125.0 (Maximum)	
Phase	Real Medium 10 kHz S.E. Corr.	Value	Phase	Real Medium 20 kHz S.E. Corr.	Value	Phase	Real Medium 40 kHz S.E. Corr.	Value
Master		20.73	Master		-1.786	Master		-10.46
	-50.00 (Minimum) 0 (Nominal) 140.0 (Maximum)			-50.00 (Minimum) 0 (Nominal) 50.00 (Maximum)			-30.00 (Minimum) 0 (Nominal) 30.00 (Maximum)	
Phase	Quad Medium 10 kHz S.E. Corr.	Value	Phase	Quad Medium 20 kHz S.E. Corr.	Value	Phase	Quad Medium 40 kHz S.E. Corr.	Value
Master		-105.8	Master		-34.20	Master		11.45
	-1300 (Minimum) 0 (Nominal) 1300 (Maximum)			-650.0 (Minimum) 0 (Nominal) 650.0 (Maximum)			-350.0 (Minimum) 0 (Nominal) 350.0 (Maximum)	

Master: Calibration out of date 5-Oct-2001 20:22

Hostile Litho-Density Sonde / Equipment Identification

Primary Equipment:

Hostile Litho Density Sonde	HLDS - D	45
Hostile Litho Density High Voltage	HLDV - D	35
Gamma Source Radioactive	GSR - Z	1846

Auxiliary Equipment:

Hostile Litho Density Pad	HLDP - C	45
Hostile Litho Density High Voltage Housi	HEH - H	35

Nuclear Porosity Lithology Cartridge - B / Equipment Identification

Primary Equipment: NPLC Cartridge	NPLC - B	79
Auxiliary Equipment: NPLC Housing	NPH - B	82

Hostile Natural Gamma Ray Sonde / Equipment Identification

Primary Equipment: HNGS Sonde	HNGS - BA	77
Auxiliary Equipment: HNGS Sonde Housing Gamma Source Radioactive	HNSH - BA GSR - U	79 135

Hostile Natural Gamma Ray Sonde Wellsite Calibration

Detector 1 Check

Phase	Na 511 Peak Loc	Value	Phase	Na 511 Peak Res %	Value	Phase	High Voltage V	Value
Master		40.65	Master		16.98	Master		1208
Before		40.63	Before		16.69	Before		1207
After		40.56	After		16.31	After		1208
	37.50 (Minimum) 40.00 (Nominal) 42.50 (Maximum)			12.00 (Minimum) 15.50 (Nominal) 19.00 (Maximum)			900.0 (Minimum) 1150 (Nominal) 1600 (Maximum)	
Phase	Na 1785 Peak Loc	Value	Phase	Na 1785 Peak Res %	Value	Phase	Temperature DEGC	Value
Master		145.2	Master		8.982	Master		33.02
Before		145.2	Before		9.496	Before		27.12
After		144.9	After		9.778	After		31.28
	135.0 (Minimum) 142.6 (Nominal) 150.3 (Maximum)			7.000 (Minimum) 8.500 (Nominal) 11.00 (Maximum)			-28.89 (Minimum) 15.50 (Nominal) 60.00 (Maximum)	
Phase	Na Count Rate CPS	Value						
Master		40.11						
Before		41.75						
After		39.73						
	10.00 (Minimum) 45.00 (Nominal) 100.0 (Maximum)							
Master: 10-Jun-2003 9:13			Before: 8-Apr-2003 2:33			After: 11-Jun-2003 21:45		

Hostile Natural Gamma Ray Sonde Wellsite Calibration

Detector 2 Check

Phase	Na 511 Peak Loc	Value	Phase	Na 511 Peak Res %	Value	Phase	High Voltage V	Value
Master		40.56	Master		17.13	Master		1234
Before		40.51	Before		16.55	Before		1235
After		40.64	After		16.78	After		1234
	37.50 (Minimum) 40.00 (Nominal) 42.50 (Maximum)			12.00 (Minimum) 15.50 (Nominal) 19.00 (Maximum)			900.0 (Minimum) 1150 (Nominal) 1600 (Maximum)	
Phase	Na 1785 Peak Loc	Value	Phase	Na 1785 Peak Res %	Value	Phase	Temperature DEGC	Value
Master		144.4	Master		9.188	Master		32.54
Before		144.2	Before		9.586	Before		26.30
After		144.7	After		9.068	After		31.70
	135.0 (Minimum) 142.6 (Nominal) 150.3 (Maximum)			7.000 (Minimum) 8.500 (Nominal) 11.00 (Maximum)			-28.89 (Minimum) 15.50 (Nominal) 60.00 (Maximum)	
Phase	Na Count Rate CPS	Value						
Master		40.04						
Before		41.81						
After		39.37						
	10.00 (Minimum) 45.00 (Nominal) 100.0 (Maximum)							

Hostile Natural Gamma Ray Sonde Wellsite Calibration		
Ratio Of Detector 1 To Detector 2		
Phase	Coincidence Count Rate Ratio	Value
Master		1.001
Before		0.9991
After		1.008
	0.9500 (Minimum)	1.050 (Maximum)
Master: 10-Jun-2003 9:13		
Before: 8-Apr-2003 2:33		
After: 11-Jun-2003 21:45		

Hostile Natural Gamma Ray Sonde Master Calibration								
Detector 1 Calibration								
Phase	Na 511 Peak Set Point	Value	Phase	Th Peak Loc	Value	Phase	Th Peak Res %	Value
Master		41.00	Master		209.0	Master		8.425
	38.00 (Minimum)	42.00 (Maximum)		201.0 (Minimum)	218.3 (Maximum)		5.000 (Minimum)	9.000 (Maximum)
Phase	Background Count Rate CPS	Value	Phase	Gain Ratio	Value			
Master	EXCEEDS LIMIT	19.30	Master		0.9783			
	20.00 (Minimum)	265.0 (Maximum)		0.9400 (Minimum)	1.060 (Maximum)			
Master: 10-Jun-2003 8:55								

Hostile Natural Gamma Ray Sonde Master Calibration								
Detector 2 Calibration								
Phase	Na 511 Peak Set Point	Value	Phase	Th Peak Loc	Value	Phase	Th Peak Res %	Value
Master		41.00	Master		209.4	Master		8.230
	38.00 (Minimum)	42.00 (Maximum)		201.0 (Minimum)	218.3 (Maximum)		5.000 (Minimum)	9.000 (Maximum)
Phase	Background Count Rate CPS	Value	Phase	Gain Ratio	Value			
Master	EXCEEDS LIMIT	18.75	Master		0.9823			
	20.00 (Minimum)	265.0 (Maximum)		0.9400 (Minimum)	1.060 (Maximum)			
Master: 10-Jun-2003 8:55								

<p>Company: Lamont Doherty</p> <p>Well: ODP Leg 209, Site 1272A</p> <p>Field: Mid Atlantic Ridge</p> <p>Country: </p> <p>Ocean: Atlantic</p>	
<p>Phasor Induction</p> <p>Natural Gamma Ray</p>	